


SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:			
PART NO: LCB1608-330Y-N				DWG.NO: TE9811301			
CUSTOMER PART NO:				CUST.DWG.NO:			
(1) DIMENSIONS (UNIT: mm) 				A	1.6 ± 0.2		m/m
				B	0.8 ± 0.2		m/m
				C	0.8 ± 0.2		m/m
				D	0.3 ± 0.2		m/m
				E			m/m
				F			m/m
				G			m/m
				H			m/m
				I			m/m
				J			m/m
(2) ELECTRICAL REQUIREMENTS							
Z (Ω)	33 ± 25%	TEST FREQ	100MHz/100mV				
RDC (Ω)	0.03 (MAX)	TEST FREQ					
IDC (mA)	3000 (MAX)	TEST FREQ					
TEST INSTRUMENTS HP4338A MILLIOHMMETER HP4291B RF IMPEDANCE/MATERIAL ANALYZER				APPROVED BY <div style="text-align: right;">吳載敏</div>			
				CHECKED BY <div style="text-align: right;">張明德</div>			
				DRAWN BY <div style="text-align: right;">黃慧診</div>			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER :				DATE :					
PART NO: LCB1608-330Y-N				DWG.NO: TE9811301					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
				A	B	C	D		
FREQ	100MHz /100mV								
SPEC	33 ± 25%	0.03 (MAX)	3000 (MAX)	1.6 ± 0.2	0.8 ± 0.2	0.8 ± 0.2	0.3 ± 0.2		
1	29.8	0.010	OK	1.60	0.82	0.81	0.33		
2	28.3	0.010	OK	1.60	0.81	0.82	0.33		
3	27.9	0.009	OK	1.61	0.82	0.82	0.28		
4	28.8	0.009	OK	1.61	0.82	0.83	0.32		
5	27.5	0.009	OK	1.61	0.84	0.81	0.30		
6	30.0	0.009	OK	1.62	0.83	0.82	0.32		
7	29.3	0.009	OK	1.62	0.84	0.81	0.33		
8	30.7	0.009	OK	1.63	0.81	0.82	0.29		
9	30.4	0.009	OK	1.63	0.83	0.81	0.31		
10	29.4	0.008	OK	1.64	0.81	0.83	0.30		
X	29.21	0.009		1.62	0.82	0.82	0.31		
R	3.20	0.002		0.04	0.03	0.02	0.05		
						APPROVED BY			
						吳載敏			
						CHECKED BY			
						張明德			
						DRAWN BY			
						黃慧診			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

LCB1608-330Y-N

